## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources							
Supplier's name or trade mark: DC							
Supplier's address: Einkauf, Gewerbestraße 10, DE							
Model identifier: LED9MG4L/2							
Type of light so	urce:						
Lighting technol	ogy used:	LED	Non-directional or directional:	NDLS			
Light source cap-type		G4					
(or other electri	c interface)						
Mains or non-mains:		NMLS	Connected light source (CLS):	Nein			
Colour-tuneable light source:		Nein	Envelope:	-			
High luminance light source:		Nein					
Anti-glare shield:		Nein	Dimmable:	Only with specific dimmers			
Product parameters							
Parameter V		Value	Parameter	Value			
General product parameters:							
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		2	Energy efficiency class	G			
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		140 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700			
On-mode power (P <sub>on</sub> ), expressed in W		1,5	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00			
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	90			
Outer dimensions	Height	24	Spectral power distribution in the	See image in last page			
	Width	24					

without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	Depth	8	range 250 nm to 800 nm, at full-load			
Claim of equivalent power <sup>(a)</sup>		-	If yes, equivalent power (W)	-		
			Chromaticity	0,468		
			coordinates (x and y)	0,422		
Parameters for LED and OLED light sources:						
R9 colour rendering index value		55	Survival factor	0,90		
the lumen maintenance factor		0,70				

(a)'-': not applicable;

(b)<sub>'-'</sub> : not applicable;

